Structure Cabling

Patch Cord

Patch Panel

Jacks & Plugs

Keystone Faceplate & Surface Box

Optic Series

M245

CAT 5e keystone jack for RJ45.



- Meet ISO/IEC 11801,TIA/EIA568C.
- Own patent products.
- Used for Wall Plate.
- Fit for wires AWG22-26.
- IDC omsertopm life 200 cycles.
- Plug insertion life 750 cycles Min .
- Dielectric strength:When applied AC 750V or DC 1000V 1 minute between adjacent terminal NO change.
- Material:Using PC/ABS for cover, PC for module, phosphor bronze for IDC wire post.

M245-1





M245-3















M245-5/6

CAT6/6A Keystone jack without using tools.

Own patent products.

Order Information:

PART Number	Descriptioa
M245-5	Cat6
M245-6	Cat6A

M255 Cat6 keystone jack.

- Meet ISO/IEC 11801,TIA/EIA568C.
- Own patent products.
- Used for Wall Plate.
- Fit for wires AWG22-26.
- IDC omsertopm life 200 cycles.
- Plug insertion life 750 cycles Min.
- Dielectric strength: When applied AC 750V or DC 1000V 1 minute between adjacent terminal NO change.
- Material:Using PC/ABS for cover,PC for module, phosphor bronze for IDC wire post.
- Cat.6 keystone jack 180°.

M255A-1

Cat.5e keystone jack.



- Meet ISO/IEC 11801.TIA/EIA568C.
- Used for Wall Plate.
- Fit for wires AWG22-26.
- IDC omsertopm life 200 cycles.
- Plug insertion life 750 cycles Min.
- Dielectric strength:When applied AC 750V or DC 1000V 1 minute between adjacent terminal NO
- Material:Using PC/ABS for cover,PC for module, phosphor bronze for IDC wire post.
- Cat.5e keystone jack 180°.

M256

Telephone jack.



- Own patent products.
- For voice system.
- Contact with gold plated.
- Fit for wire AWG22-26.

M268

Cat.5e keystone jack Shielded



- Meet ISO/IEC 11801,TIA/EIA568C.
- Half shlelded.
- Cat.5e 180°Half Shielded.
- Color: Black.

M247

Cat.5e keystone jack shielded.





- Meet ISO/IEC 11801,TIA/EIA568C.
- Cat.5e 90°Fully Shielded.

M243

CAT5e Keystone jack shielded.



- Meet ISO/IEC 11801,TIA/EIA568C
- Own patent products.
- Fit for wires AWG22-26
- IDC omsertopm life 200 cycles
- Plug insertion life 750 cycles Min
- Dielectric strength: When applied AC 750V or DC 1000V
 1 minute between adjacent terminal NO change
- Material:Using PC/ABS for cover,PC for module,phosphor bronze for IDC wire post.

M253

CAT6 Keystone jack shielded.



- Meet ISO/IEC 11801,TIA/EIA568C.
- Own patent products.
- Fit for wires AWG22-26.
- IDC omsertopm life 200 cycles.
- Plug insertion life 750 cycles Min .
- Dielectric strength: When applied AC 750V or DC 1000V
 1 minute between adjacent terminal NO change.
- Material: Using PC/ABS for cover,PC for module,phosphor bronze for IDC wire post.

M254

CAT6 Keystone jack shielded.



- Meet ISO/IEC 11801,TIA/EIA568C.
- Own patent products.
- Fit for wires AWG22-26.
- IDC omsertopm life 200 cycles.
- Plug insertion life 750 cycles Min.
- Dielectric strength: When applied AC 750V or DC 1000V
 1 minute between adjacent terminal NO change.
- Material: Using PC/ABS for cover,PC for module,phosphor bronze for IDC wire post.

M264

CAT6A Keystone jack shielded.



- Meet ISO/IEC 11801,TIA/EIA568C.
- Own patent products.
- Fit for wires AWG22-26.
- IDC omsertopm life 200 cycles.
- Plug insertion life 750 cycles Min .
- Dielectric strength: When applied AC 750V or DC 1000V
 1 minute between adjacent terminal NO change.
 Material: Using PC/ABS for cover, PC for module, phosphor
- bronze for IDC wire post.

M221

Modular Cord Coupler 8P8C Without Wire UTP CAT5E RJ45-RJ45 Coupler





UTP CAT5E RJ45-RJ45 Coupler







M224

UTP CAT6 RJ45-RJ45 Coupler



M225

UTP Cat.5e keystone jack coupler RJ45-RJ45



M226

UTP Cat6 keystone jack coupler RJ45-RJ45



M227

FTP Cat.5e keystone jack coupler RJ45-RJ45



M228

FTP Cat6 keystone jack coupler RJ45-RJ45



M230

In-line Connection box

